





MasterSeal Roof 2689

Crack-bridging, spray applied, mechanically, chemically and highly wear resistant 2-C-Polyurea waterproofing system, ETA-17/0508 accor. to ETAG 005 part 6

			Consumption Approx.
	Primer	MasterSeal P 770 (for concrete) (depends on substrate, consult Technical Service please)	0.3 – 0.5 kg/m ²
	Waterproofing Liquid applied	MasterSeal M 689 Pigmented, 2-component 100% pure Polyurea, spray applied	min. 2.4 kg/m ²
	Topcoat (optional)	MasterSeal TC 269 Pigmented, two component, UV- and weather resistant, elastic PU topcoat, solvent containing	1 x 0.15-0.20 kg/m ²

Note: Consumptions are indicative and may be higher, depending on substrate roughness, temperature and porosity, as well as waste produced during application.




MasterSeal Roof 2689

Crack-bridging, spray applied, mechanically, chemically and highly wear resistant 2-C-Polyurea waterproofing system, ETA-17/0508 accor. to ETAG 005 part 6

CE-MARKING ETAG 005

CE	
1119	
Master Builders Solutions Deutschland GmbH Donnerschweer Str. 372, D-26123 Oldenburg	
03	
468901	
ETAG 005- Teil 6	
Liquid applied roof waterproofing kits based on polyurethane resin	
Water vapour diffusion resistance factor μ	480
Resistance to wind loads	> 50 kPa
Resistance to spreading fire and radiant heat	NPD
Reaction to fire	Broof-T4
Statement on dangerous substances	Does not contain any
Working life	W3
Climatic zones	M und S
Imposed loads	P1 bis P4
Roof slope	S1 bis S4
Lowest surface temperature	TL 4
Highest surface temperature	TH 4



MasterSeal Roof 2689

Crack-bridging, spray applied, mechanically, chemically and highly wear resistant 2-C-Polyurea waterproofing system, ETA-17/0508 accor. to ETAG 005 part 6

DISCLAIMER

In view of widely varying site conditions and fields of application of our products, this technical data sheet is meant to provide general application guidelines only. This information is based on our present knowledge and experience. The customer is not released from the obligation to conduct careful testing of suitability and possible application for the intended use. The customer is obliged to contact the technical helpline for fields of application not expressly stated in the technical data sheet under "Fields of Application". Use of the product beyond the fields of application as stated in the technical data sheet without previous consultation with Master Builders Solutions and possible resulting damages are in the sole responsibility of the customer. All descriptions, drawings, photographs, data, ratios, weights i.e. stated herein can be changed without advance notice and do not represent the condition of the product as stipulated by contract. It is the sole responsibility of the recipient of our products to observe possible proprietary rights as well as existing laws and provisions. The reference of trade names of other companies is no recommendation and does not exclude the use of products of similar type. Our information only describes the quality of our products and services and is no warranty. Liability is accepted for incomplete or incorrect particulars in our data sheets only in the event of intent or gross negligence, without prejudice to claims under product liability laws.

Master Builders Solutions Deutschland GmbH
Donnerschweer Straße 372
26123 Oldenburg
Germany

System build-up MasterSeal Roof 2689 – January 21
Version 01